




## Farm Hand A/P Tractor (R-1)

Tube Type – Nylon

SIZE	P.R.	CODE	SKID DEPTH	TREAD WIDTH	O.D.	C.S.	RIM	MAX. INFL.	MAX. LOAD	WT.
8.3-24 TT	6	RF-03	31/32	7.9	38.8	8.3	7.0 x24	34	1610	47
9.5-24 TT	6	RF-05	33/32	8.7	41.2	9.5	8.0 x24	30	1870	59
11.2-24 TT	6	RF-07	36/32	10.7	42.0	11.5	10.0 x24	26	2090	76
12.4-24 TT	8	RF-09	38/32	11.8	44.0	12.5	11.0 x24	32	2830	88
13.6-24 TT	8	RF-11	42/32	13.4	47.8	14.3	12.0 x24	28	3080	102
14.9-24 TT	8	RF-13	42/32	14.0	49.2	14.8	13.0 x24	26	3520	118
11.2-28 TT	6	RF-15	32/32	10.4	46.9	11.1	10.0 x28	26	2200	80
12.4-28 TT	8	RF-17	38/32	11.8	49.6	12.5	11.0 x28	32	3000	99
13.6-28 TT	8	RF-19	42/32	12.5	52.0	13.2	12.0 x28	28	3300	112
14.9-28 TT	8	RF-21	42/32	14.6	54.6	15.2	13.0 x28	26	3740	120
16.9-28 TT	8	RF-23	43/32	16.7	57.0	17.6	15.0 x28	24	4300	151
16.9-30 TT	10	RF-25	43/32	16.9	59.0	17.6	15.0 x30	28	4940	154
18.4-30 TT	10	RF-27	45/32	17.9	61.0	18.7	16.0 x30	26	5520	202
18.4-34 TT	10	RF-29	45/32	18.0	64.1	18.4	16.0 x34	26	6000	205
11.2-38 TL	8	RF-31	36/32	10.7	57.0	11.2	10.0 x38	32	2720	97
11.2-38 TT	8	RF-33	36/32	10.7	57.0	11.2	10.0 x38	32	2720	98
12.4-38 TT	8	RF-57	42/32	11.8	58.8	12.5	11.0 x38	32	3520	127
13.6-38 TT	8	RF-59	45/32	12.6	61.1	13.4	12.0 x38	28	3740	157
15.5-38 TT	10	RF-35	45/32	14.8	61.0	15.4	14.0 x38	30	4050	145
18.4-38 TT	10	RF-37	45/32	18.0	68.0	18.4	16.0 x38	26	6400	229

- The Denman Farm Hand A/P Tractor has quickly been recognized as a “BEST VALUE” in the Farm Community
- Prolific Size Array enables Fitment to Very Broad Range of Tractors and enables dealers to always have the right tire for the customer



## Farm Hand Irrigation (R-1)

Tube Type – Nylon – Flap Included

SIZE	P.R.	CODE	SKID DEPTH	TREAD WIDTH	O.D.	C.S.	RIM	MAX. INFL.	MAX. LOAD	WT.
11.2-24 TT (SET)	4	RF-39	36/32	10.8	42.0	11.5	10.0 x24	18	1650	76
11.2-38 TT	4	RF-41	36/32	10.7	57.0	11.2	10.0 x38	18	2090	93
14.9-24 TT	6	RF-43	42/32	14.0	49.2	14.8	13.0 x24	20	3000	112

Tire, Tube & Flap (Set)