



## Farm Hand Implement (I-1)

Tubeless and Tube Type – Nylon

SIZE	P.R.	CODE	SKID DEPTH	TREAD WIDTH	O.D.	C.S.	RIM	MAX. INFL.	MAX. LOAD	WT.
9.5L-14 TT	8	IF-01	8/32	8.8	29.0	9.4	7.0 x 14	44	2400	26.5
9.5L-14 TL	8	IF-03	8/32	8.8	29.0	9.4	7.0 x 14	44	2400	27
11L-14 TT	8	IF-15	8/32	9.8	29.4	10.8	8.0 x 14	36	2470	28
11L-14 TL	8	IF-17	8/32	9.8	29.4	10.8	8.0 x 14	36	2470	29
6.70-15 TT	8	IF-31	7/32	6.0	27.5	6.6	4.5 x 15	60	2010	18
6.70-15 TL	8	IF-33	7/32	6.0	27.5	6.6	4.5 x 15	60	2010	18
7.60-15 TT	8	IF-35	8/32	6.8	28.7	7.5	5.5 x 15	52	2090	23
7.60-15 TL	8	IF-37	8/32	6.8	28.7	7.5	5.5 x 15	52	2090	23
9.5L-15 TT	8	IF-05	11/32	9.0	30.0	9.8	7.0 x 15	44	2470	28
9.5L-15 TL	8	IF-07	11/32	9.0	30.0	9.8	7.0 x 15	44	2470	29
11L-15 TT	8	IF-09	11/32	9.9	31.2	10.8	8.0 x 15	36	2540	30
11L-15 TL	8	IF-11	11/32	9.9	31.2	10.8	8.0 x 15	36	2540	32
11L-15 TL	12	IF-13	11/32	9.9	31.2	10.8	8.0 x 15	52	3200	33
12.5L-15 TT	12	IF-23	11/32	11.1	12.1	12.1	10.0 x 15	52	3860	40
12.5L-15 TL	12	IF-25	11/32	11.1	12.1	12.1	10.0 x 15	52	3860	41
11L-16 TT	10	IF-19	11/32	9.9	10.8	10.8	8.0 x 16	44	3000	33
11L-16 TL	10	IF-21	11/32	9.9	10.8	10.8	8.0 x 16	44	3000	35
12.5L-16 TT	10	IF-27	11/32	11.2	12.3	12.3	10.0 x 16	44	3680	43
12.5L-16 TL	14	IF-29	11/32	11.2	12.3	12.3	10.0 x 16	56	4180	45

■ *Designed for Free Rolling Wheels on wagons and trailers, the Denman Farm Hand is a proven performer*

25 M.P.H. Max. Speed.

\*Tubeless tires may be used with a tube.

